

TECHNICAL DATA SHEET

VELADURA METALIZADA TRANSPARENTE

REF: VMT

1. DESCRIPTION:

Water-based finish to provide a metallic decorative effect.

2. PROPERTIES:

- Quick dry
- Elastic behavior
- High chemical resistance
- Not containing solvents

3. APPLICATIONS:

- On any surface
- Indoors and outdoors
- To use preferably a metallic trowel for its application.

4. CHARACTERISTICS:

Appearance:	Humid paste
Color	Variable
Odor	Weak
Solubility in water	100%
Density	aprox. 1.8 gr/cm ³
Volatile percentage	80 / 85
pH	8 / 9
Application temperature	+ 5°C to + 30°C
Toxicity	No

TECHNICAL DATA SHEET

VELADURA METALIZADA TRANSPARENTE

REF: VMT

5. TECHNICAL SPECIFICATIONS:

Presentation:	Plastic bottles of 5 or 1 litre
Application temperature:	+ 5°C a + 30°C.
Drying time:	3-4 hours a 20°C /60% relative humidity.
Flashpoint:	No flammable.
Expiration:	One year from the date of production, in original container.
Security:	No dangerous.
Storage:	Avoid abrupt and excessive temperature changes.
Performance:	Approx. 10 a 12 m2.

6. PERFORMANCE:

- Surface must be clean, and free of dust.
- To ensure the correct homogenization of the mixture (to shake well the mixture).
- Application with a metallic trowel.
- To emphasize the movements (water-textured) of the material to achieve better metallic effect.

7. EFFICIENCY:

- Repainting: 16 hours
- Performance: 10-12 m²/ kg depending of the nature of the surface.

8. STORAGE:

- For proper conservation, save it in a cool place avoiding both the cold and the excessive heat.
- Shake well before using.
- Deadline for storage in original unopened packaging: 6 months.