

TECHNICAL DATA SHEET

ZINC KIT

REF: KZN

1. DESCRIPTION:

It is a metallic mineral based on Eco Cement, metal particles of natural zinc, mineral fillers and nano additive (Component A).

Mixing it with Resimet (Component B) a coating is formed with fine texture for high traffic areas with a thickness of 1 to 3 mm, available in different finishes, with different application techniques.

It is applicable on any surface thanks to its adhesion, resulting continuous surfaces seamless, thanks to its flexibility and resistance to UV rays.

It is suitable for walls and furniture. Its use is intended for both indoor and outdoor.

2. PRESENTATION

Package kits in bicomponent formats

12 kg Zinc + 4 lts of Resimet
6 kg Zinc + 2 lts of Resimet
3 kg Zinc + 1 lts of Resimet
1kg Zinc + 0,5 lts of Resimet

Drying time	3-4 hours at 20°C / 60% relative humidity
Flash point	Non-flammable
Expiration	1 year from the date in original container
Safety	Not dangerous.
Storage	Avoid sudden and excessive changes of temperature
Mixing ratio by volumen	2 parts of powder Zinc to 1 part Resimet

3. APPLICATION RECOMMENDATIONS:

- The base must be completely dry and free of moisture.
- Always respect the same dosage.
- Application temperature: 10-25 ° C.

TECHNICAL DATA SHEET

ZINC KIT

REF: KZN

4. CHARACTERISTICS OF EMPLOYMENT:

- Pot life: 8 hours.
- Dry to touch: 60 min.
- To repaint: About 8 hours.
- Total Drying: 24 hours.

* These times can vary considerably depending on the temperature

5. PERFORMANCE:

- Specific gravity: 8.0 g / cm³
- Viscosity: 25-100-120 sec.
- Bulk density: 2.00 - 4.00 g / ml

* These results are of standard assays and may vary depending on the conditions of placing.

6. SURFACES:

The surface must be clean, dry and dust free, no loosened parts or breaks.

7. PRECAUTIONS:

- Not change the mixing ratio.
- Use within 90 minutes of preparation.
- Do not apply at temperatures below 5°C or above 35°C.
- Store in cool place.