

# TECHNICAL DATA SHEET

## VELADURA METALIZADA NEGRO

REF: VMN

### 1. DESCRIPTION:

Water-based finish to provide a black metallic decorative effect.

### 2. PROPERTIES:

- Quick dry
- Elastic behavior
- High chemical resistance
- Not containing solvents

### 3. APPLICATIONS:

- On any surface
- Indoors and outdoors
- To use preferably a metallic trowel for its application.

### 4. CHARACTERISTICS:

|                         |                               |
|-------------------------|-------------------------------|
| Appearance:             | Humid paste                   |
| Color                   | Variable                      |
| Odor                    | Weak                          |
| Solubility in water     | 100%                          |
| Density                 | aprox. 1.8 gr/cm <sup>3</sup> |
| Volatile percentage     | 80 / 85                       |
| pH                      | 8 / 9                         |
| Application temperature | + 5°C to + 30°C               |
| Toxicity                | No                            |

# TECHNICAL DATA SHEET

## VELADURA METALIZADA NEGRO

REF: VMN

### 5. TECHNICAL SPECIFICATIONS:

|                                 |                                                              |
|---------------------------------|--------------------------------------------------------------|
| <b>Presentation:</b>            | Plastic bottles of 5 or 1 litre                              |
| <b>Application temperature:</b> | + 5°C a + 30°C.                                              |
| <b>Drying time:</b>             | 3-4 hours a 20°C /60% relative humidity.                     |
| <b>Flashpoint:</b>              | No flammable.                                                |
| <b>Expiration:</b>              | One year from the date of production, in original container. |
| <b>Security:</b>                | No dangerous.                                                |
| <b>Storage:</b>                 | Avoid abrupt and excessive temperature changes.              |
| <b>Performance:</b>             | Approx. 10 a 12 m2.                                          |

### 6. PERFORMANCE:

- Surface must be clean, and free of dust.
- To ensure the correct homogenization of the mixture (to shake well the mixture).
- Application with a metallic trowel.
- To emphasize the movements (water-textured) of the material to achieve better metallic effect.

### 7. EFFICIENCY:

- Repainting: 16 hours
- Performance: 10-12 m<sup>2</sup>/ kg depending of the nature of the surface.

### 8. STORAGE:

- For proper conservation, save it in a cool place avoiding both the cold and the excessive heat.
- Shake well before using.
- Deadline for storage in original unopened packaging: 6 months.