

TECHNICAL DATA SHEET

SEALER L

REF: SL

1. DESCRIPTION OF THE PRODUCT:

Sealer L it is a water-based bonding for Cement and pore sealer.

2. ADVANTAGES OF SEALER L

- Completely transparent.
- High elasticity, with a high rate of recovery.
- Elastic behavior.
- Slight residual tack.
- Good resistance to alkalis.

3. TECHNICAL SPECIFICATIONS

Packaging	5 Lts of liquid
Drying time	3-4 hours at 20° C / 60% RH
Flamming point	Non-flammable
Expiring time	1 year, from the date of manufacture, in its original container
Safety	Not Dangerous
Storage	To avoid sudden changes in temperature
Performance	50 - 60 sqm

4. CHEMICAL PROPERTIES

Composition	Aqueous dispersion of an acrylic copolymer
Appearance	White liquid
Weight	1.04 (Kg/L.)
Solids content	60 ± 1%
PH value.	3.5 - 5.5
Viscosity	<3000 mPas
Tg. (°C.)	- 10
TMFP. (°C.)	0



Av. Río Guadalquivir,2
28906- Getafe (Madrid)
(+34) 911 407 965
info@cementdesign.eu

TECHNICAL DATA SHEET

SEALER L

REF: SL