

TECHNICAL DATA SHEET

RESIMET

REF: RM

1. DESCRIPTION:

Water-based binder resin neutral color, free of VOC, as component B for Metallic Collection

2. ADVANTAGES OF RESIMET

- Completely transparent.
- High elasticity, with a high rate of recovery.
- Elastic behavior.
- Slight residual tack.
- Good resistance to alkalis.
- High chemical resistance

3. TECHNICAL SPECIFICATIONS

Package kits in different formats

Resimet 4 L
Resimet 2 L
Resimet 1 L
Resimet 0,5 L

Installation temperature	+ 5°C to + 30°C
Drying time	3-4 hours at 20° C / 60% RH
Flamming point	Non-flammable
Expiring time	1 year, from the date of manufacture, in its original container
Safety	Not Dangerous
Storage	Avoid sudden changes in temperature
Performance	10-15 sqm

TECHNICAL DATA SHEET

RESIMET

REF: RM

4. CHEMICAL PROPERTIES:

Composition	Aqueous dispersion of an acrylic copolymer
Appearance	White liquid
Weight	1.08 (Kg/L)
Solids content	25 ± 1%
PH value.	9
Viscosity	<3000 mPas
Tg. (°C.)	- 10
TMFP. (°C.)	0