

Av. Río Guadalquivir,2 28906- Getafe (Madrid) (+34) 911 407 965 info@cementdesign.eu

# TECHNICAL DATA SHEET RESICEM

REF: RN

# 1. DESCRIPTION:

Water-based binder resin neutral color, free of VOC, as component B for eco cements.

### 2. ADVANTAGES OF RESICEM:

- Fully transparent.
- Impact-resistance.
- Elastic behavior.
- High chemical resistance.
- Good resistance to alkalis.

### 3. TECHNICAL SPECIFICATIONS:

**Presentation**: Plastic containers in different sizes:

Resicem 7.2 liters Resicem 3.6 liters Resicem 1.8 liters Resicem 0.6 liters

**Temperature application:** + 5°C a + 30°C.

**Drying time:** 3-4 hours a 20°C /60% relative humidity.

Flashpoint: No flammable.

**Expiration:** One year from the date of production, in original container.

**Security:** No dangerous.

**Storage:** Avoid abrupt and excessive temperature changes.

**Performance:** Approx. 10 a 12 m2.



Av. Río Guadalquivir,2 28906- Getafe (Madrid) (+34) 911 407 965 info@cementdesign.eu

# **TECHNICAL DATA SHEET**RESICEM

REF: RN

# 4. CHEMICAL PROPERTIES:

**Composition:** Aqueous acrylic copolymer resin.

Appearance:White liquidSpecific weight:1.01 (Kg/l.).

**Value pH.:** 7.5.

 Viscosity:
 50-250 cps.

 Tg. (°C.):
 -10.

 TMFP.(°C.):
 0