

# TECHNICAL DATA SHEET

## VELADURA METALIZADA COBRE

REF: VMC

### 1. DESCRIPTION:

Water-based finish to provide a metallic decorative effect.

### 2. PROPERTIES:

- Quick dry
- Elastic behavior
- High chemical resistance
- Not containing solvents

### 3. APPLICATIONS:

- On any surface
- Indoors and outdoors
- To use preferably a metallic trowel for its application.

### 4. CHARACTERISTICS:

<b>Appearance:</b>	Humid paste
<b>Color</b>	Variable
<b>Odor</b>	Weak
<b>Solubility in water</b>	100%
<b>Density</b>	aprox. 1.8 gr/cm <sup>3</sup>
<b>Volatile percentage</b>	80 / 85
<b>pH</b>	8 / 9
<b>Application temperature</b>	+ 5°C to + 30°C
<b>Toxicity</b>	No

# TECHNICAL DATA SHEET

## VELADURA METALIZADA COBRE

REF: VMC

### 5. TECHNICAL SPECIFICATIONS:

<b>Presentation:</b>	Plastic bottles of 5 or 1 litre
<b>Application temperature:</b>	+ 5°C a + 30°C.
<b>Drying time:</b>	3-4 hours a 20°C /60% relative humidity.
<b>Flashpoint:</b>	No flammable.
<b>Expiration:</b>	One year from the date of production, in original container.
<b>Security:</b>	No dangerous.
<b>Storage:</b>	Avoid abrupt and excessive temperature changes.
<b>Performance:</b>	Approx. 10 a 12 m <sup>2</sup> .

### 6. PERFORMANCE:

- Surface must be clean, and free of dust.
- To ensure the correct homogenization of the mixture (to shake well the mixture).
- Application with a metallic trowel.
- To emphasize the movements (water-textured) of the material to achieve better metallic effect.

### 7. EFFICIENCY:

- Repainting: 16 hours
- Performance: 10-12 m<sup>2</sup>/ kg depending of the nature of the surface.

### 8. STORAGE:

- For proper conservation, save it in a cool place avoiding both the cold and the excessive heat.
- Shake well before using.
- Deadline for storage in original unopened packaging: 6 months.