

TECHNICAL DATA SHEET

RESIFLEX

REF: RNF

1. DESCRIPTION

Water-based binder resin neutral color, free of VOC, as component B for eco cements.

2. ADVANTAGES OF RESIFLEX:

- Fully transparent.
- Impact-resistance.
- Elastic behavior.
- High chemical resistance.
- Good resistance to alkalis.

3. TECHNICAL SPECIFICATIONS:

Presentation:	Plastic containers in different sizes: Resiflex 10 liters Resiflex 5 liters Resiflex 2.5 liters Resiflex 0.850 liters
Temperature application:	+ 5°C a + 30°C
Drying time:	3-4 hours a 20°C /60% relative humidity.
Flashpoint:	No flammable.
Expiration:	One year from the date of production, in original container.
Security:	No dangerous.
Storage:	Avoid abrupt and excessive temperature changes.
Performance:	Approx. 15 a 20 m2

TECHNICAL DATA SHEET

RESIFLEX

REF: RNF

4. CHEMICAL PROPERTIES:

Composition:	Aqueous acrylic copolymer resin.
Appearance:	White liquid
Specific weight:	1.01 (Kg/l.).
Value pH.:	7.5.
Viscosity:	50-250 cps.
Tg. (°C.):	-10.
TMFP.(°C.):	0